



## INTRODUCTION

SiSiB® LR8240 is high strength type two-component liquid silicone rubber for injection molding process . High performance elastomeric parts could be got through Mixing A: B =1: 1.

## KEY FEATURES

Highly transparency

Excellent process ability

High strength

20,30, 40, 50, 60, 70 durometer grades available

ROHS and FDA test passed

## TYPICAL PHYSICAL PROPERTIES

Product	SiSiB® LR8240 HCE
Appearance	Transparent
Curing Condition	130°C×5min, A:B=1:1
Hardness (Shore A)	40+/-3
Tensile Strength (MPa)	Min. 8.0
Elongation (%)	Min. 600
Tear Strength (KN/m)	Min. 24.0

## APPLICATIONS

Swimming goggles

Keypads

Kitchenwares

Parts

**Power Chemical**  
ISO9001 ISO14001 certificated

Copyright© 2008 Power Chemical Corporation Ltd.  
SiSiB® is a registered trademark of PCC. For more knowledge regarding organosilanes, you may visit [www.SiSiB.com](http://www.SiSiB.com) or [www.PCC.asia](http://www.PCC.asia)



## PACKING AND STORAGE

SiSiB<sup>®</sup> LR8240 is supplied in 20Kg can or 200Kg drum.

Store in a cool and dry place out of direct sunlight.

## NOTES

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

Please send all technical questions concerning quality and product safety to: [support@SiSiB.com](mailto:support@SiSiB.com).